ThinLine II Reader

Low Profile Proximity Card Reader • 5395 (Wiegand) 5398 (Clock-and-Data)



ACCESS reliability.

Application

Providing performance and reliability, HID's attractive, unobtrusive ThinLine® II proximity card reader is housed in a two-piece, weatherproof secure potted enclosure.

Features

- Easily installed and maintained with the use of replaceable covers.
- Available with a Wiegand or Clock-and-Data interface.
- Provides high reliability, consistent read range and low power consumption.
- ▶ Features include multicolor LED and internal control or host control of the LED and beeper.
- ▶ Mounts directly on metal with minimal impact on the read range performance.
- Aesthetic design available in two cover designs and four colors to match any décor.
- Includes multilingual installation manual.

Mounting

Mounts on a single-gang electrical box for easy installation. Mounts directly on metal with minimal impact on read range performance.

Audiovisual Indication A red LED flashes green and the beeper sounds when reader is presented with a proximity card. The multicolor LED and beeper can also be controlled individually by the host system.

Diagnostics

On reader power-up, an internal self-test routine checks and verifies the setup configuration, determines the internal or external control of the LED and beeper and initializes reader operation. An additional external loop-back test allows for the reader outputs and inputs to be verified without the use of additional test equipment.

Indoor/outdoor Design Sealed in a rugged, weatherized polycarbonate enclosure designed to withstand harsh environments, providing reliable performance and a high degree of vandal resistance.

Easily Interfaced

Wiegand output model interfaces with all existing Wiegand protocol access control systems. Clock-and-Data (magnetic stripe) model interfaces with most systems that accept magnetic stripe readers.

Security

Recognizes card formats up to 85 bits, with over 137 billion unique codes.

Warranty

Lifetime warranty against defects in materials and workmanship (see complete sales policy for details).


Part Numbers


Base Part No.: 5395 Wiegand interface Base Part No.: 5398 Clock-and-Data interface Description: Tri-State LED, internal beeper on

Options

- · CLASSIC series cover in white, beige, charcoal gray or black
- · Designer series cover in white, wave blue, charcoal gray or black
- LED and beeper operation

(Please see "How to Order Guide" for a description of the options and associated part numbers.)





Typical Maximum* Read Range

ProxCard® II card - up to 5.5" (14 cm) ISOProx® II card - up to 5" (12.7 cm) DuoProx® II card - up to 5" (12.7 cm) Proximity & MIFARE® card - up to 5" (12.7 cm)
Proximity & MIFARE® card - up to 5" (12.7 cm)
ProxCard® Plus card - up to 1.5" (3.8 cm)
ProxKey® II keyfob - up to 2" (5.1 cm)
MicroProx® Tag - up to 3" (7.6 cm) *Depending on local installation conditions.

Dimensions:

4.70" x 3.00" x 0.68" (11.9 x 7.6 x 1.7 cm)

Material: Polycarbonate UL 94

Power supply:

Linear power supplies are recommended.

Current requirements:

Average: 30 mA (5 VDC); 20 mA (12 VDC) Peak: 110 mA (5 VDC); 115 mA (12 VDC)

Operating temperature:

° to 150° F (-30° to 65° C)

Operating humidity:

95% relative humidity non-condensing

Weight:

3.3 oz. (94 gm)

Transmit frequency: 125 kHz

Excite frequency: 125 kHz

Cable distance:


Wiegand interface: 500 feet (150 m) Clock-and-data interface: 50 feet (15 m)


Recommended cable is ALPHA 1295 (22 AWG) 5 conductor minimum stranded with overall shield or equivalent. Additional conductors may be required for LED or beeper control.

Environmental: IP55


Certifications:

UL294/cUL (US), FCC Certification (US), IC (Canada), CE (EU), C-tick (Australia, New Zealand), SRRC (China), MIC (Korea), NCC (Taiwan), MIC (Japan), iDA (Singapore), RoHS





© 2009 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 05/2009



MKT-PTHINLINEii_DS_EN

hidglobal.com

ACCESS experience.

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico

Tel: +52 477 779 1492 Fax: +52 477 779 1493

Europe, Middle East & Africa Haverhill Business Park Phoenix Road Haverhill, Suffolk CB9 7AE England Tel: +44 (0) 1440 714 850 Fax: +44 (0) 1440 714 840



Phone: 1-800-351-9962 Fax: 1-312-212-1800

About BarcodesInc

Who We Are

BarcodesInc is North America's leading provider of •] ^& \hat{a} \hat{a}

We Owe Our Success To You

Why Choose BarcodesInc?

Dedicated Account A UbU[Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

Highly-Trained Technical Support

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same & È

Premier Access to Top Manufacturers

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

Responsive Customer Service

Every phone call and email is responded to promptly, completely and accurately by our customer service & æ È

Easy Returns

Damaged, defective or incorrectly ordered goods may be returned without hassle.

BRANDS





Intermec

Honeywell

ODATALOGIC.











unitech





Microsoft*



symbol*

AND MORE