

ProxPro® II Reader

125 kHz Proximity

New Generation Proximity Card Reader • 5455 (Wiegand), 5458 (Clock-and-Data)



ACCESS reliability.

Application

HID's ProxPro® II proximity reader for access control combines performance, reliability, and ease of installation into a two-piece, weatherproof potted enclosure. International users will appreciate the multilingual installation manual, lower voltage requirement and flexible mounting options.

Features

- Two-piece reader design allows for easy installation.
- Available with a Wiegand or Clock-and-Data interface.
- Provides high reliability, consistent read range and low power consumption.
- Features include multicolor LED and internal or host control of the LED and beeper.
- Mounts directly on metal with minimal impact on the read range performance. Optional kit enables mounting behind glass.

Feature	ProxPro	ProxPro II
Multilingual installation manual	No	Yes
Glass mounting kit (optional)	Yes	Yes
Supply Voltages	12V and 24V	5V and 12V
Voltage Range min/max	10 / 28.5VDC	5 / 16VDC
Current Draw avg/peak	100 / 120 mA	25 / 125 mA
Read Range at 12VDC (Proxcard® II/ISOProx® II)	8" (20 cm) / 7" (17 cm)	9" (22 cm) / 8" (20cm)
IP Rating	IP55	IP55
European/Asian mounting holes	No	Yes (vertical)
Weatherproofing method	Rubber O ring	Fully potted electronics
Cover installation method	4 screws, then snap in bezel	Snap on cover
Custom molded logo	No	Available (one-time tooling charge)
Termination method	Screw Terminals	Wire Pigtail
Metal compensation	Jumper	No, but provides equivalent performance on metal
LED/Beeper configuration	DIP Switch or Command Card	Command Card
Custom Firmware	Socketed Processor, change part	Order from factory
Tamper Switch	Yes	No, but electronics are potted to prevent tampering
Keypad Version available	Yes	No
Wiegand Pullup Select 5 or 12V	DIP Switch	No
Serial Version available	Yes	No

Compare features of the ProxPro II to the original ProxPro reader (still available):

Installation	Easy, streamlined installation procedure is consistent with HID's ThinLine® II, MiniProx® and ProxPoint® Plus readers. Included installation manual features instructions in English, French, German, Spanish, Portuguese, Chinese and Japanese.
Mounting	Mounts on a single-gang electrical box for easy installation. Mounting holes are provided for European and Asian J-boxes. Mounts directly on metal with minimal impact on read range performance. An optional kit enables mounting behind glass.
Audiovisual Indication	An LED flashes green and the beeper sounds when a proximity card is presented to the reader. The multicolor LED and beeper can also be controlled individually by the host system.
Diagnostics	On reader power-up, an internal self-test routine checks and verifies the setup configuration, determines the internal or external control of the LED and beeper and initializes reader operation. An additional external loop-back test allows for the reader outputs and inputs to be verified without the use of additional test equipment.
Indoor/outdoor Design	Sealed in a rugged, weatherized polycarbonate enclosure designed to withstand harsh environments, providing reliable performance and a high degree of vandal resistance. Two-piece reader design allows for easy installation.
Easily Interfaced	Wiegand output model interfaces with all existing Wiegand protocol access control systems. Clock-and-Data (magnetic stripe) model interfaces with most systems that accept magnetic stripe readers.
Security	Recognizes card formats up to 84 bits, with over 1.93x10 ²⁵ unique codes.
Warranty	Lifetime warranty against defects in materials and workmanship (see complete sales policy for details).
Options	<ul style="list-style-type: none"> • Termination: 18" (45 cm) pigtail standard, 9' (2.7m) available by special order. • Mounting: glass mounting kit available separately • Color: white, beige, charcoal gray or black • LED and beeper operation
Part Numbers	Base Part Number: 5455 Wiegand Base Part Number: 5458 Clock-and-Data interface
Description	Tri-State LED, internal beeper on Glass Mount Kit: 5455AGM00

Please see "How to Order Guide" for a description of the options and associated part numbers. The How to Order Guide can be downloaded in PDF format from: www.hidcorp.com/support.

Typical Maximum* Read Range
 ProxCard® II card - up to 9" (22 cm)
 ISOProx® II card - up to 8" (20 cm)
 DuoProx® II card - up to 8" (20 cm)
 Smart ISOProx® card - up to 8" (20 cm)
 Smart DuoProx® card - up to 8" (20 cm)
 HID Proximity and MIFARE® card - up to 8" (20 cm)
 ProxCard® Plus card - up to 4" (10 cm)
 ProxKey® II keyfob - up to 4" (10 cm)
 MicroProx® Tag - up to 4" (11 cm)
 *Depending on local installation conditions.

Dimensions:
 5.00" x 5.00" x 1.00"
 (12.7 x 12.7 x 2.54 cm)

Material: Polycarbonate UL 94

Power supply:
 5-16 VDC
 Linear power supplies are recommended.

Current requirements:
 Average: 25 mA at 12 VDC
 Peak: 125 mA at 12 VDC

Operating temperature:
 -22° to 150° F (-30° to 65° C)

Operating humidity:
 0-95% relative humidity non-condensing


Weight: 13.6 oz. (385 g)

Transmit frequency: 125 kHz
Excite frequency: 125 kHz

Environmental: IP54

Certifications:
 UL294/cUL (US), FCC Certification (US), IC (Canada), CE (EU), C-tick (Australia, New Zealand), SRRC (China), MIC (Korea), NCC (Taiwan), MIC (Japan), iDA (Singapore), RoHS

Cable distance:
 Wiegand interface: 500 feet (150 m)
 Clock-and-Data interface: 50 feet (15 m)
 Recommended cable is ALPHA 1295 (22 AWG) 5 conductor minimum stranded with overall shield or equivalent. Additional conductors may be required for LED or beeper control.



© 2009 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 05/2009



MKT-PROXPROII_DS_EN



ACCESS experience.

hidglobal.com

HID Global Offices:

Corporate North America
 15370 Barranca Pkwy
 Irvine, CA 92618
 U.S.A.
 Phone: (800) 237-7769
 Phone: +1 (949) 732-2000
 Fax: +1 (949) 732-2360

Asia Pacific
 19/F 625 King's Road
 North Point
 Island East
 Hong Kong
 Phone: +852 3160-9800
 Fax: +852 3160-4809

Latin America
 Circunvalacion Ote. #201 B
 Despacho 2
 Col. Jardines del Moral
 Leon 37160, Gto.
 Mexico
 Phone: +52 477 779 1492
 Fax: +52 477 779 1493

Europe, Middle East & Africa
 Phoenix Road
 Haverhill, Suffolk
 CB9 7AE
 England
 Phone: +44 (0) 1440 714 850
 Fax: +44 (0) 1440 714 840



About BarcodesInc

Who We Are

BarcodesInc is North America's leading provider of... [The following text is intentionally obscured with noise for this block]

We Owe Our Success To You

Our success is due to the support of our customers... [The following text is intentionally obscured with noise for this block]

Why Choose BarcodesInc?

Dedicated Account A UbU Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

Highly-Trained Technical Support

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same day.

Premier Access to Top Manufacturers

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

Responsive Customer Service

Every phone call and email is responded to promptly, completely and accurately by our customer service team.

Easy Returns

Damaged, defective or incorrectly ordered goods may be returned without hassle.

BRANDS



AND MORE