

# AY-U900

## UHF Integrated Long-Range Reader



THE AY-U900 IS AN RFID LONG-RANGE PROXIMITY CARD READER THAT IS COMPATIBLE WITH MULTIPLE PROTOCOLS AND CAN READ MULTIPLE TAG FORMATS.

THE READER IS WATERPROOF AND IS SUITABLE FOR USE IN A WIDE RANGE OF RFID APPLICATIONS, SUCH AS TRANSPORT MANAGEMENT, VEHICLE MANAGEMENT, CAR PARKING, PRODUCTION PROCESS CONTROL, AND ACCESS CONTROL.

### GENERAL DESCRIPTION

The AY-U900 is the solution for security situations that require a long-range proximity reader. The reader is both easy to install and easy to use.

### MAIN FEATURES

- Read range up to 12 m (39.4 ft) (adjustable)\*
- Read Sensitivity: Dual polarization read mode

### PROFESSIONAL GRADE FEATURES

- Wiegand 26-Bit (Custom: Wiegand 34-Bit)
- Comes with an installation bracket kit and RS-232 cable
- Weatherproof (IP-54)
- Maximum Cable Distance: 150 m (500 ft)

# SPECIFICATIONS

## ELECTRICAL SPECIFICATIONS

■ Operating Voltage Range	9 to 12 VDC (2 A)
■ Input Current	Standby: 0.2 A max, Read: 1.2 A max
■ Card Read Distance	Up to 12 m (39.4 ft) (adjustable) * Read range was tested with Rosslare's AT-T910 card
■ Transmission Protocol	Wiegand 26-Bit (Custom: Wiegand 34-Bit)
■ Maximum Cable Distance	150 m (500 ft)
■ Frequency	AY-U900US: 902–928 MHz (America) AY-U900C: 920–925 MHz (China) AY-U900EU: 865–868 MHz (Europe)
■ Read Sensitivity	Dual polarization read mode
■ Cards and Tags	Rosslare's AT-T910 and AT-T911 ISO18000-6B Tags EPC GEN2 (ISO18000-6C) Tags

## ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	-20°C to 80°C (-4°F to 176°F)
■ Operating Temperature	-40°C to 125°C (-40°F to 257°F)
■ Operating Humidity	0 to 95% (non-condensing) Suitable for outdoor use (IP54)

## PHYSICAL SPECIFICATIONS

■ Dimensions	44 x 44 x 5 cm (17.32 x 17.32 x 2 in.)
■ Weight	2.32 kg (5.11 lb)

## SYSTEM COMPONENTS

The AY-U900 is compatible with standard access controllers.

## PRODUCT WARRANTY

5-year Limited Product Warranty