



MicroLatch™

Microlatch FOB-4B



FOB-4B - Four-button RF Keyfob (Metallic Finish)

Features:

A non-biometrics 4-button RF keyfob, offering simple user authentication and access control. Convenient communication via RF transmission which removes the need for physical keys or contact and prox cards. An alternative to the fingerprint based BIO-13, BIO-14, BIO-15 and FOB-13, this elegant keyfob offers standard low-cost security and access control with simplicity and flexibility. Compatible with the REC-18 and most rolling-code receiver systems with Keeloq™ encryption.

FOB-4B is also a multi-purpose, four-channel output Keyfob which allows long range RF communication connectivity for numerous access control and Smart Home applications, such as carpark access and alarm panel activation. It can simultaneously activate up to 4 independent door locks and/or devices (via compatible multi-channel receivers).



MicroLatch

Specifications

Operating Voltage	:	12VDC
Battery Type	:	12V 27A Alkaline cell x 1
Current Consumption	:	TBA
Number of Channel	:	4 (Four-Button)
Operating Frequency	:	433.92MHz SAW Resonator Locked (+/- 74KHz)(Long Range)
Transmission Modulation	:	AM ASK
Transmission Security	:	Keeloq™ Code Hopping Technology
RF Range	:	100m Typical (Environment dependant)
Operating temperature range	:	-10 C to 50 C
Certifications	:	C-Tick, CE Approvals All product features and specifications are correct at the time of publication, and are subject to change without notice.