



MA 3006 - IP based Fingerprint Access Control (IP 65 for outdoor)

Specifications:

Fingerprint Capacity	1000 templates
ID card Capacity	10,000
Transaction Capacity	30,000
Hardware Platform	ZEM700
Sensor	Optical Sensor
Algorithm Version	Finger v9.0
Communication	RS232/485, TCP/IP, USB-host
Access Control Interface for	3rd party electric lock, door sensor, exit button, alarm
Wiegand Signal	Input & Output
Optional Functions	Mifare
Display	N/A
Power Supply	12V DC
Operating Temperature	-10 °C- 50 °C
Operating Humidity	10%-90%
Index of Protection	IP65
Dimension(W*H*D)mm	73*148*34.5
Gross Weight	1.15kg



- * 1 touch a-second user recognition
- * Stores 1,000 templates, 10,000 cards and 30,000 transactions
- * Reads Fingerprint and/or Card
- * Optional integrated smart card reader
- * Built-in Serial and Ethernet ports
- * Tamper-proofs switch and alarm outputs
- * Request-to-exit and alarm contacts
- * Real-time 1-touch data export 3rd party hosted & non-hosted applications
- * Audio prompt for enrollment and deletion of the user
- * Audio-Visual indications for acceptance and rejection of valid/invalid fingers
- * IP65 protection index