

Infinite detail with HD and 20x zoom

1.3 Megapixel HD PTZ dome cameras with 20x optical zoom



1.3Megapixel HD 20x PTZ Dome Network Camera

SNP-5200/5200H

The SNP-5200/5200H are high performance 1.3 megapixel PTZ cameras and provide 20x optical zoom in HD images. These fully ONVIF compliant PTZ domes feature multiple resolutions and aspect ratios from CIF (320 x 240) up to full 1.3 megapixel (1280 x 1024) including High Definition (16:9) format at 720p. They also provide the ability to stream different resolutions simultaneously allowing the most relevant stream to be transmitted to your viewing or recording device at the same time. The SNP-5200H incorporates an IP66 housing able to withstand extreme environments from -58°F to +122°F (-50°C ~ +50°C).

- Max. 1.3M (1280 x 1024) Max. resolution
- Supports 16:9 HD (720p)
- 20x optical zoom Day/Night lens
- 0.7Lux min. illumination
- H.264 / MPEG-4 / MJPEG multiple codecs
- Hybrid (Analog video out and control)
- PoE Plus, SD memory slot, 2-way Audio, IP66 and IK10 (SNP-5200H)


1.3Megapixel HD 20x PTZ Dome Network Camera

SNP-5200/5200H



Dimensions

Unit : mm (inch)



Specifications

	SNP-5200N/P	SNP-5200HN/HP
VIDEO		
Imaging Device	1/3" 1.3M PS CMOS	
Total Pixels	1,384(H) x 1,076(V)	
Effective Pixels	1,329(H) x 1,049(V)	
Scanning System	Progressive	
Min. Illumination	Color : 0.7Lux (F1.6, 50IRE), 0.01Lux (Sens-up 60x, 50IRE) B/W : 0.08Lux (F1.6, 50IRE), 0.001Lux (Sens-up 60x, 50IRE)	
S / N Ratio	52dB	
Video Output	CVBS : 1.0 Vp-p / 75Ω composite, 704 x 480(N), 704 x 576(P), for installation	
LENS		
Focal Length (Zoom Ratio)	4.45 ~ 89mm (20x)	
Max. Aperture Ratio	F1.6(Wide) / F2.9(Tele)	
Angular Field of View	H : 56.56°(Wide) ~ 3.10°(Tele) / V : 43.32°(Wide) ~ 2.34°(Tele)	
Min. Object Distance	1m (3.28ft)	
Focus Control	AF / One-shot AF / Manual	
Lens Type	DC auto iris	
Mount Type	Board-in type	
PAN / TILT / ROTATE		
Pan Range	360° Endless	
Pan Speed	Preset : 500°/sec, Manual : 0.024°/sec ~ 120°/sec	
Tilt Range	190°(-5° ~ 185°)	
Tilt Speed	Preset : 500°/sec, Manual : 0.024°/sec ~ 120°/sec	
Preset	255ea	
Preset Accuracy	±0.1°	
OPERATIONAL		
Camera Title	Off / On (Displayed up to 15 characters)	
Day & Night	Auto (ICR) / Color / B/W	
Backlight Compensation	Off / BLC / HLC	
Contrast Enhancement	SSDR (Samsung Super Dynamic Range) (Off / On)	
Digital Noise Reduction	SSNR III (2D+3D noise filter) (Off / On)	
Digital Image Stabilization	Off / On	
Motion Detection	Off / On (4 programmable zones)	
Privacy Masking	Off / On (8 programmable zones)	
Sens-up (Frame Integration)	Off / Auto (2x ~ 60x)	
Gain Control	Off / Low / Medium / High / Manual	
White Balance	ATW / AWC / Manual / Indoor / Outdoor	
Electronic Shutter Speed	Auto / A.FLK / Manual (1/30 ~ 30,000sec)	
Digital Zoom	16x	
Flip / Mirror	Off / On	
Intelligent Video Analytics	Scene Change, Virtual Line, Enter / Exit, Appear / Disappear	
Alarm I/O	Input 4ea / Output 2ea (Relay)	
Remote Control Interface	RS-485/422	
RS-485 Protocol	Samsung-T/E, Pelco-P/D, Panasonic, Honeywell, AD, Bosch, Vicon, GE	
NETWORK		
Ethernet	RJ-45 (10/100BASE-T)	
Video Compression Format	H.264, MPEG-4, MJPEG	
Resolution	1280 x 1024, 1280 x 720P (HD), 1024 x 768, 800 x 600, 640 x 480, 320 x 240	
Max. Framerate	30fps at all resolutions	
Video Quality Adjustment	H.264, MPEG-4 : Compression level, Target bitrate level control MJPEG : Quality level control	
Bitrate Control Method	H.264, MPEG-4 : CBR or VBR, MJPEG : VBR	
Streaming Capability	Multiple streaming (Up to 10 profiles)	
Audio I/O	Mic / Line in, Line out	
Audio Compression Format	G.711 u-law	
Audio Communication	Bi-directional audio	
IP	IPv4, IPv6	
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, ONVIF HTTPS(SSL) login authentication, Digest login authentication	
Security	IP address filtering, User access log, 802.1x authentication	
Streaming Method	Unicast / Multicast	
Max. User Access	10 users at unicast mode	
Memory Slot	SD/SDHC memory slot	
ONVIF Conformance	Yes	
Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatian, Hungarian, Greek	
Web Viewer	Supported OS : Windows XP / VISTA / 7, MAC OS Supported Browser : Internet Explorer 6.0 or Higher, Firefox, Google Chrome, Apple Safari	
Central Management Software	NET-i viewer	
ENVIRONMENTAL		
Operating Temperature / Humidity	-10°C ~ +50°C (+14°F ~ +122°F) / 20% ~ 80% RH	-50°C ~ +50°C (-58°F ~ +122°F) / up to 100% RH
Ingress Protection	N/A	IP66 and IK10 Grade (Waterproof)
ELECTRICAL		
Input Voltage	24V AC, PoE+ (IEEE802.3at)	
Power Consumption	Max. 21W	Max. 25W (Heater off), Max. 52W (Heater on) * Heater works at AC input only.
MECHANICAL		
Color / Material	Ivory / Plastic	
Dimensions (WxH)	Ø155.0 x 243.4mm (Ø6.1" x 9.58")	
Weight	2.1Kg (4.63 lb)	

Accessories (Optional)



SAMSUNG TECHWIN AMERICA Inc.
100 Challenger Road, Suite 700, Ridgefield Park, NJ 07660, UNITED STATES
Toll Free : 1-877-213-1222 Fax : 1-201-373-0124
www.samsungsecurityusa.com



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.
Design and specifications are subject to change without notice.

■ DISTRIBUTED BY



www.asi.ind.in