



QMXI-P10T

Professional Mini Indoor Speed Dome Camera (QMXI Series/10x)

Compact, Reliable and Easy to use



1. Fast & Silent Motion

- No Accumulative Error with Preset Function
- Shortest Path By Vector Drive Technology
- High Accuracy with Micro-Stepping Control Technology
- Smooth Motion at High Zoom Magnification Mode
- Lighting Speed (max 360⁰/Sec) & Smooth Manual Speed (MIN. 0.05⁰/Sec)
- Lowest Noise & Lowest Vibration
- Endless 360⁰/Sec Pan Rotation

2. Superior Zoom Camera

- 100x Zoom Control (Optical 10x, Digital 10x), WDR
- Day & Night (IR Cut-filter)

3. Powerful Functions

- Independent Preset Characteristic Setup (AE, WB and etc)
- 128 Preset Positions with Alphanumeric Labels
- 4 Patten, 8 Swing and 8 Group Functions
- 4 Privacy Zones (Spherical Coordinates)
- Auto Flip, Auto Parking, Power-up Action
- On Screen Display On/Off
- Built-in Sensor In/Out Function (4 In / 2 Out)
- 4.5\" - Small in Size
- Vandal-Proof (Dome Cover : PC / Housing & Accessories : AL)
- Optional Network Function (IP Addressable)

www.markglobal.in

Specifications:

Model	QMXI-P10C	
Signal Format	PAL	
Camera	Image Device	Sony 1/4" Interline Transfer CCD
	Total Pixel	470K Pixels [795(H) x 596(V)]
	Effective Pixel	440K Pixels [752(H) x 582(V)]
	H. Resolution	500 TV Lines(Color), 570 TV Lines(B/W)
	S/N Ratio	50dB (AGC Off)
	Zoom	10x Optical Zoom and 10x Digital Zoom
	Focal Length	F1.8, f=3.8 ~ 38mm
	MIN. Illumin.	0.7 Lux (Color) / 0.02 Lux (B/W) @ 50 IRE
	Day & Night	Auto / Day / Night (IR Cut Filter)
	Focus	Auto / Manual / Semi-Auto
	Iris	Auto / Manual
	Shutter Speed	128x ~ 1/120000 sec
	AGC	Normal / High / Off
	White Balance	Auto / Manual (Red & Blue Gain Adjustable)
	BLC	Low / Middle / High / Off
	Flicker less	Selectable
	SSNR	Low / Middle / High / Off
	Other Functions	Frame Freeze Function, System Image Flip by Installation Type
	Pan/Tilt	Range
Tilt : 180°(Auto -Flip On) , 95°(Auto -Flip Off)		
Pan/Tilt Speed		Preset : 360° sec
		Manual : 0.05~ 360° sec (Zoom Proportional)
		Swing : 1~ 180° sec
Preset		128 Presets with Labels / Independent Preset Characteristic Setup
Pattern		4 Patterns (Approx. 5 Minutes for Each Pattern)
Swing		8 Swings
Group	8 Groups (MAX. 20 Entries for Each Group)	
Other Functions	Image Auto Flip, Auto Parking, Power-up Action & etc.	
General	Communication	RS-485
	Protocol	Pelco-D, Pelco-P Selectable
	Privacy Zone	4 Zones
	Sensor In/Out	Built-in 4 Input
	OSD	English On / Off
	Fan/Heater	Built-in
	Power	DC Type : DC 12V / 2.5A(Default)
		AC Type : AC 24V / 1.5A(Optional)
	Dimension	Dome : ø 115 mm / 4.5"
		Housing : 190(ø) x 263(H) x 297(W) mm / 7.5" (ø) x 10.4" (H) x 11.7"(W)
Weight	Approx. 3.8 Kg / 8.4 Lbs	
Operating Temp.	-30°C ~ 50°C / -22°F ~ 122°F	