

DH-DVR2104/2108/2116H

4/8/16 All Channel 2CIF Mini 1U Standalone DVR



Features

- > Up to 4/8/16 cameras with 1080p realtime preview
- > H.264 dual-stream video compression
- > DVR2104/2108/2116H: All channel 2CIF
- > HDMI / VGA / TV simultaneous video output
- > All channel synchronous realtime playback, GRID interface & smart search
- > 3D intelligent positioning with Dahua PTZ dome camera
- > Support 1 SATA HDD up to 4TB, 2 USB2.0

Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

Technical Specifications

Model	DH-DVR2104H	DH-DVR2108H	DH-DVR2116H
System			
Main Processor	Embedded processor		
Operating System	Embedded LINUX		
Video			


DH-DVR2104/2108/2116H

Input	4 channel, BNC	8 channel, BNC	16 channel, BNC	
Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)			
Audio				
Input	1 channel, RCA			
Output	1 channel, RCA			
Two-way Talk	Reuse audio input/output channel 1			
Display				
Interface	1 HDMI, 1 VGA, 1 TV, BNC(1.0Vp-p, 75Ω)			
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768, 800×600			
Display Split	1/4	1/4/8/9	1/4/8/9/16	
Privacy Masking	4 rectangular zones (each camera)			
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording			
Recording				
Video/Audio Compression	H.264 / G.711			
Resolution	D1(704×576/704×480)/2CIF(704×288/704×240)/CIF(352×288/352×240)/QCIF(176×144/176×120)			
Record Rate	Main Stream:	D1(1~6/7fps)/2CIF(1~25/30fps)/2ch@D1+2ch@CIF(1~25/30fps)	D1(1~6/7fps)/2CIF(1~25/30fps)/2ch@D1+6ch@CIF(1~25/30fps)	D1(1~6/7fps)/2CIF(1~25/30fps)/2ch@2D1+14ch@CIF(1~25/30fps)
	Extra Stream	CIF(1~6/7fps)/QCIF(1~25/30ps)		
Bit Rate	48~4096Kb/s			
Record Mode	Manual, Schedule(Regular(Continuous), MD), Stop			
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec			
Video Detection				
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Buzzer & Screen tips			
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank			
Playback & Backup				
Sync Playback	1/4	1/4/9	1/4/9/16	
Search Mode	Time/Date, MD & Exact search (accurate to second)			

DH-DVR2104/2108/2116H

Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
Network	
Ethernet	RJ-45 port (10/100M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	1 SATA port, up to 4TB
Auxiliary Interface	
USB Interface	2 ports (1 Rear), USB2.0
RS485	PTZ control
General	
Power Supply	DC12V/2A
Power Consumption	10W(without HDD)
Working Environment	-10 ~ +55°C / 10~90%RH / 86~106kpa
Dimension(W×D×H)	Mini 1U, 325mm×245mm×45mm
Weight	1.5KG(without HDD)

System Connection



Takes DVR2116H as an example

DH-DVR2104/2108/2116H

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815 Email:

overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2013 Dahua Technology Co., Ltd.