



Active System Integration

CP-TAP-MY10C-ET

Horizontal Resolution of 550 TVL

www.asi.ind.in



Features

- 1/4" CCD
- High Resolution of 550 TVL
- 10x Optical Zoom
- Manual Pan Speed 0.1°~250°/s, Tilt speed 0.1°~60°/s
- 360° continuous panning
- 128 presets, OSD menu
- 4 pattern tour, 2 auto scan
- Inbuilt surge protection and power off recovery, IP66

Technical Specification

Image Sensor	1/4" CCD
Pixels	NTSC:768(H)x494(V) PAL:752(H)x582(V)
Resolution	550 TVL
Minimum Illumination	0.01 Lux @F1.2
S/N Ratio	more than 50dB
Electronic Shutter	1/50~1/120,000s
Zoom Optical	10x
Lens	3.7~37 mm
Focus Mode	Auto/Manual
Gamma	0.45
White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Special Functions	OSD, Camera Title, Auto Scan, Auto Cruise
Pan Range	360 ° endless



Active System Integration

www.asi.ind.in

Technical Specification

Pan Speed	0.1°~250°/s
Tilt Range	90°(180° auto flip)
Tilt Speed	0.1°~60°/s
Proportional Pan/Tilt Control	Yes
Number of Presets	128
Communication	RS 485, Protocol: Pelco-P/D, Baud Rate: 2400~19200 bps
Sync. System	Internal
Video Output	1.0 Vp-p/75W
Power Supply	DC 12V ± 5%
IP Rating	IP66
Operating Temp	0°C~40°C
Certifications	CE, FCC and RoHS Certified