



Active System Integration

CP-UAP-SC23C

Horizontal Resolution of 540 TVL

www.asi.ind.in



Features

- 1/4" CCD
- High Resolution of 540 TVL
- Powerful 23x optical zoom
- Day/Night (ICR), 2D-DNR, Auto iris, Auto focus, AWB, AGC, BLC
- Max 300 °/s pan speed, 360° continuous pan rotation and auto flip with no blind spot monitor
- Up to 255 Presets, 5 Auto Pattern, 8 Auto Tour, 5 auto scan

Technical Specification

| | |
|----------------------|-----------------------------------|
| Image Sensor | 1/4" CMOS |
| Pixels | 640H) × 480(V) |
| Resolution | 540 TVL |
| Minimum Illumination | 0.5 Lux@F1.6 |
| S/N Ratio | more than 50dB |
| Electronic Shutter | 1/50s~1/10,000s |
| Zoom Optical | 23x |
| Lens | 3.9 ~ 89.7 mm |
| White Balance (AWB) | Auto/Manual |
| Gain Control (AGC) | Auto/Manual |
| Back Light Comp. | ON/OFF |
| Day & Night (ICR) | Yes |
| Special Functions | 4000V thunder and wave protection |



Active System Integration

www.asi.ind.in

Technical Specification

| | |
|-------------------|-------------------------------------------------------------------------------------|
| Pan Range | Horizontal: 0°~360°endless, Vertical: -2°~90° auto flip 180° to continue monitor |
| Tilt Range | Horizontal: 0°~360°endless, Vertical: -2°~90° auto flip 180° to continue monitor |
| Number of Presets | 255 |
| Preset Speed | Horizontal: 300°/s, Vertical: 180°/s |
| Surge Protection | yes |
| Alarm | Input: 2, Output: 1 |
| Video Output | CVBS: 1.0Vp-p / 75Ω |
| Power Supply | DC 12V ± 5% |
| Power Consumption | 15W(Indoor), 27W(Outdoor, heater on) |
| IP Rating | IP66 |
| Dimensions | Φ222(mm) x 322(mm) |
| Weight | Weight 5.0kg |
| Operating Temp | -40°C ~ 60°C |
| Certifications | CE, FCC and RoHS Certified |