



Active System Integration

## CP-UAP-SY23C-EH

Horizontal Resolution of 600 TVL

www.asi.ind.in



### Technical Specification

Image Sensor	1/4" Super HAD CCD II
Pixels	PAL: 752(H) x 582(V) NTSC: 768(H) x 494(V)
Resolution	600 TVL
Minimum Illumination	0.01 Lux/F1.6
S/N Ratio	more than 50dB
Electronic Shutter	Auto: 1/s~1/100,000s Manual: 1/s~1/10,000s
Iris Control	Auto Iris
Zoom Optical	23x
Zoom Digital	16x
Lens	3.9 mm~89.7mm
Focus Mode	Auto
Gamma	0.45
White Balance (AWB)	AAWB (3000 to 7500K), ATW(2000 to 1000K), Indoor(3200K), Outdoor(5800K), Manual
Gain Control (AGC)	Auto/Manual

### Features

- 1/4" Super HAD CCD II
- High Resolution of 600 TVL
- Min. Illumination of 0.01Lux@F1.6
- Powerful 23x Optical Zoom
- Day/Night (ICR), 2D-DNR, Auto iris, Auto focus, AWB, AGC, BLC
- Up to 255 presets, 5 auto scan, 8 tour, 5 pattern



Active System Integration

www.asi.ind.in

## Technical Specification

Back Light Comp.	ON/OFF
Day & Night (ICR)	Yes
Special Functions	Day/Night (ICR), D-WDR, DNR (2D&3D), D-WDR, Auto iris, Auto focus, AWB, AGC, BLC
Pan Range	Horizontal: 0°~360°endless, Vertical: -2°~90° auto flip 180° to continue monitor
Pan Speed	Horizontal: 0.1°~300°/s
Tilt Speed	Vertical:0.1° ~150°/s
Number of Presets	255
Preset Speed	Horizontal: 300°/s, Vertical: 180°/s
Surge Protection	Yes
Alarm	2/1 alarm input/output, triggering Preset/Tour/Pattern/Scan/Alarm output
Video Output	CVBS: 1.0Vp-p / 75ohm
Power Supply	AC 24V/1.5A(±10%)
Power Consumption	15W(Indoor), 27W(Outdoor, heater on)
IP Rating	66
Dimensions	Φ222(mm) x 322(mm)
Weight	5.0kg
Operating Temp	-40°C ~ 60°C
Certifications	CE, FCC and RoHS