



Active System Integration

CP-UAP-SY23CL6

Horizontal Resolution of 600 TVL

www.asi.ind.in



Technical Specification

| | |
|----------------------|--|
| Image Sensor | 1/4" Sony Super HAD II CCD |
| Pixels | PAL: 752(H) x 582(V) NTSC: 768(H) x 494(V) |
| Resolution | 600 TVL |
| Minimum Illumination | 0.01 Lux@F1.6 |
| S/N Ratio | more than 50dB |
| Electronic Shutter | Auto: 1/s~1/100,000s Manual: 1/s~1/10,000s |
| Iris Control | Auto Iris |
| Zoom Optical | 23x |
| Zoom Digital | 16x |
| Lens | 3.9 mm~89.7mm |
| Focus Mode | Auto |
| Gamma | 0.45 |
| White Balance (AWB) | AWB(3200to7500K), ATB(2000to10000K), Indoor(3200K), Outdoor(5800K);Manual |
| Gain Control (AGC) | Auto/Manual |
| Back Light Comp. | ON/OFF |

Features

- 1/4" Super HAD CCD II
- High Resolution of 600 TVL
- Min. Illumination of 0.01Lux@F1.6
- Powerful 23x Optical Zoom
- Day/Night (ICR), DNR (2D and 3D), D-WDR, Auto iris, Auto focus, AWB, AGC, BLC
- Up to 255 presets, 5 auto scan, 8 tour, 5 pattern



Active System Integration

www.asi.ind.in

Technical Specification

| | |
|-------------------|---|
| Back Light Comp. | ON/OFF |
| Day & Night (ICR) | Yes |
| IR LED | The max. IR distance is over 60m |
| Special Functions | Day/Night (ICR), D-WDR, DNR (2D&3D), D-WDR, Auto iris, Auto focus, AWB, AGC, BLC |
| Pan Range | Horizontal: 0°~360°endless, Vertical: -2°~90° auto flip 180° to continue monitor |
| Tilt Range | Horizontal: 0°~360°endless, Vertical: -15°~90° auto flip 180° to continue monitor |
| Number of Presets | 255 |
| Preset Speed | Horizontal: 240° /s, Vertical: 200° /s |
| Surge Protection | Yes |
| Communication | RS485 |
| Video Output | CVBS: 1.0Vp-p / 75ohm |
| Power Supply | AC 24V/1.5A(±10%) |
| Power Consumption | 13W(Indoor), 31W(Outdoor, heater on) |
| IP Rating | IP66 |
| Dimensions | Φ185(mm) x 299(mm) |
| Weight | 5.0kg |
| Operating Temp | -40°C ~ 60°C |
| Certifications | CE, FCC and RoHS |