



Active System Integration

CP-UAP-SY37C-EH

Horizontal Resolution of 600 TVL

www.asi.ind.in



Technical Specification

Image Sensor	1/4" Super HAD CCD II
Pixels	PAL: 752(H) x 582(V), NTSC: 768(H) x 494(V)
Resolution	600 TVL
Minimum Illumination	0.01 Lux/F1.6(AGC ON,Slow Shutter ON)
S/N Ratio	More than 50dB
Electronic Shutter	Auto: 1/s~1/100,000s Manual: 1/s~1/10,000s
Iris Control	Auto Iris
Zoom Optical	37x
Zoom Digital	16x
Lens	3.4mm ~ 122.4mm
Focus Mode	Auto
Gamma	0.45
White Balance (AWB)	AWB (3000 to 7500K), ATW(2000 to 1000K), Indoor(3200K), Outdoor(5800K), Manual
Gain Control (AGC)	Auto/Manual
Back Light Comp.	ON/OFF

Features

- 1/4" Super HAD CCD II
- High Resolution of 600 TVL
- Min. Illumination of 0.01 Lux/F1.6(AGC ON,Slow Shutter ON)
- Powerful 37x Optical Zoom
- Day/Night (ICR), D-WDR, DNR (2D and 3D), Auto iris, Auto focus, AWB, AGC, BLC
- Up to 255 presets, 5 auto scan, 8 tour, 5 pattern



Active System Integration

www.asi.ind.in

Technical Specification

Day & Night (ICR)	Yes
Special Functions	Day/Night (ICR), D-WDR, DNR (2D&3D), Auto iris, Auto focus, AWB, AGC, BLC
Pan Range	Horizontal: 0°~360° endless, Vertical: -2°~90° auto fl
Pan Speed	Horizontal: 0°~360° endless, Vertical: -2°~90° auto fl
Idle Motion	Activate Preset/Pan/Scan/Tour/Pattern if there is no command in the specified period
Tilt Range	0° ~ 90°, auto flip 180°
Number of Presets	255
Preset Speed	Horizontal: 240° /s, Vertical: 200° /s
Surge Protection	Yes
Communication	RS485
Video Output	CVBS: 1.0Vp-p / 75Ω
Power Supply	AC 24V/1.5A (±10%)
Power Consumption	12W(Indoor), 24W(Outdoor, heater on)
IP Rating	IP66
Dimensions	Φ186mm×234mm
Weight	5.0kg
Operating Temp	-40°C ~ 60°C
Certifications	CE, FCC and RoHS