



Active System Integration

## CP-QAC-TC62L2-D

High Resolution of 620 TVL

www.asi.ind.in



### Technical Specification

Image Sensor	High Quality Image Sensor
Pixels	PAL:752H×582V NTSC:768H×494V
Resolution	620 TVL
Minimum Illumination	0.01 lux @F1.2
S/N Ratio	More than 50dB
Electronic Shutter	1/60-1/100,000sec
Flickerless Mode	Electrical
Lens	3.6 mm Lens
Gamma Correction	0.45
White Balance (AWB)	Auto

### Features

- High Quality Image Sensor
- 620 TVL High Resolution  
lux @ F1.2
- 3.6 mm Fixed Lens
- IR Range of 20 Mtr with 24 IR  
Leds
- IP66, AGC, AWB and BLC



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

Gain Control (AGC)	Auto
Back Light Comp.	Auto
Day & Night (ICR)	Yes
IR	IR Range of 20 Mtr with 24 IR Leds
Sync	Internal Sync
Power Supply	DC 12V
Power Consumption	DC12V, 300mA
IP Rating	IP66
Weight	350g
Operating Temp	-10~ +50°C RH95% Max
Certifications	CE, FCC and RoHS