



Active System Integration

## CP-LAC-TC72L3A

High Resolution of 720 TVL

[www.asi.ind.in](http://www.asi.ind.in)



### Technical Specification

Image Sensor	High Quality Image Sensor
Pixels	PAL:720H x 480V
Resolution	720 TVL
Minimum Illumination	0.2 lux, 0 lux (IR ON)
S/N Ratio	More than 46.4dB
Lens	6 mm Lens
Gamma Correction	0.45

### Features

- High Quality Image Sensor
- 720 TVL High Resolution
- 0.2 lux @ F1.2, 0 lux (IR ON)
- 6 mm Lens
- IR Range of 30 Mtr with 25 IR Leds
- AGC, AWB and BLC



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Comp.	Auto
IR	IR Range of 30 Mtr with 25 IR Leds
Sync	Internal Sync
Power Supply	DC 12V
Power Consumption	210mA (178-242mA)
IP Rating	IP66
Dimensions	185mm x 89mm x 70mm
Weight	285g
Operating Temp	-10°C~50°C, -20°C~60°C
Certifications	CE, FCC and RoHS