



Active System Integration

CP-RAC-DC72L2

High Resolution of 720 TVL

www.asi.ind.in



Features

- High Quality Image Sensor
- 720 TVL High Resolution Camera
- Lux@F1.2(IR on)
- 3.6 mm Fixed Lens
- IR Range of 20 mtr with 24 IR LEDs
- AGC, AWB and BLC

Technical Specification

Image Sensor	High Quality Image Sensor
Pixels	PAL:765H×510V
Resolution	720 TVL
Minimum Illumination	0.1 lux @F1.2(IR on)
S/N Ratio	more than 46.4db
Electronic Shutter	1/50 - 1/100000 sec
Lens	3.6 mm
Gamma Correction	0.45



Active System Integration

www.asi.ind.in

Technical Specification

White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Comp.	Auto
IR	IR Range of 20 Mtr with 24 IR Leds
Sync	Internal Sync
Video Output	1.0Vp-p / 75Ω
Power Supply	DC12V
Power Consumption	DC12V 210 mA IR ON
Dimensions	93(Φ) x 64.4(H)mm
Weight	170g
Operating Temp	-10C ~ 50C, 14°F ~ 122°F
Certifications	CE, FCC and RoHS