



Active System Integration

CP-EAC-TY65MVER5

650 TVL High Resolution Camera

www.asi.ind.in



Technical Specification

Image Sensor	1/3" Sony Super HAD II CCD
Pixels	PAL:752Hx582V, NTSC:768Hx494V
Resolution	650 TVL
Min. Illumination	COLOR :0.3Lux(F1.2,50IRE,AGC ON) ; B/W :0.005Lux(F1.2,50IRE,AGC ON)
S/N Ratio	More than 50dB(AGC OFF)
Electronic Shutter	PAL:1/50~1/100000 Sec;NTSC:1/60~1/100000 Sec;
Iris Control	Manual Iris
Lens	9-22MM auto iris lens
White Balance (AWB)	ATW1/ATW2/AWC / MANUAL
Gain Control (AGC)	Low/Milddle/High choice
Back Light Compensation	on/off

Features

- 1 / 3" SONY SUPER HAD II CCD
- 650 TVL High Resolution Camera
- 3 Units of Dot Matrix Array LED
- Array Range of 50 meters
- 9~22mm Manual iris Lens
- With OSD, D-WDR



Active System Integration

www.asi.ind.in

Technical Specification

Day & Night (ICR)	Auto/Color/B/W/External Control
IR	3 units of Dot matrix Array LED
WDR	Digital WDR
Protocol	Pelco-D / Pelco-P/NEXTCHIP protocol
Sync	Power Synchronization / Internal Synchronization
Video Output	BNC Mode: twisted-pair method (built-in twisted pair transmission module)
Special Functions	OSD, Privacy Masking, Motion Detection
Power Supply	DC12V
Power Consumption	2.5W
IP Rating	IP66
Dimensions	260 x 185 x 100mm
Weight	1500g
Operating Temperature	-20~50°C
Certifications	CE, FCC, RoHs