



Active System Integration

## CP-EAC-TY70ML3D-E

High Resolution of 700 TVL

[www.asi.ind.in](http://www.asi.ind.in)



### Technical Specification

Image Sensor	1/3" Sony Super HAD II
Pixels	PAL:752Hx582V, NTSC:768Hx494V
Resolution	700 TVL
Min. Illumination	0 lux @F1.2
S/N Ratio	more than 48dB
Electronic Shutter	1/50(1/60) - 1/100000 Sec
Lens	6 mm
Gamma Correction	0.45

### Features

- 1/3" Sony Super HAD II
- 700 TVL High Resolution Camera
- 0 lux @ F1.2 (IR ON)
- 6 mm Fixed Lens
- IR Range of 30 Mtrs with 36 LEDs
- Powerful OSD Operational Function
- Weather Resistant IP 66 Housing
- AGC, AWB and BLC
- CE, FCC and RoHS Certified



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

White Balance (AWB)	ON/OFF Selectable
Gain Control (AGC)	ON/OFF Selectable
Back Light Compensation	ON/OFF Selectable
IR	36 LEDs, Upto 30 Mtrs
Sync	Internal/External Line Lock
Video Output	1.0 Vp-p/75 ohm
Power Supply	DC 12V $\pm$ 5%
Power Consumption	< 5W
IP Rating	IP66
Dimensions	205 x 81x 85mm
Weight	500g
Operating Temperature	-20~50°C
Certifications	CE, FCC, RoHs