



Active System Integration

CP-EAC-PY60MA

High Resolution of 600 TVL

www.asi.ind.in



Technical Specification

Image Sensor	1/3" Sony CCD
Pixels	PAL:752(H)×582(V), NTSC:768(H)×494(V)
Resolution	600 TVL
Min. Illumination	0.05 lux@F1.2
S/N Ratio	more than 48dB
Electronic Shutter	1/50(1/60) - 1/100000 Sec
Flickerless mode	ON/OFF
Lens	3.7 mm
Gamma Correction	0.45
White Balance (AWB)	Auto

Features

- 1/3" Sony 600 TVL
- High Resolution of 600 TVL
- 3.7 mm Pin Hole Lens
- 0.05 lux @ F1.2
- AGC, AES, BLC, Mirror, Privacy Masking and Motion Detection
- CE, FCC and RoHS Certified



Active System Integration

www.asi.ind.in

Technical Specification

Gain Control (AGC)	Auto
Back Light Compensation	Auto
Sync	Internal Sync
Video Output	1.0 Vp-p/75 ohm
Special Functions	OSD, Camera ID, Camera Title, Mirror, Privacy Masking=7, Motion Detection=4, 2D-DNR
Power Supply	DC 12V \pm 5%
Power Consumption	< 4W
Dimensions	36 x 36 x 15mm
Weight	130g
Operating Temperature	-10~50°C
Certifications	CE, FCC, RoHs