



Active System Integration

CP-SMR-0404Q2V

H.264 Video Compression

www.asi.ind.in



Technical Specification

Operating System	Embedded Real-time Linux
Operation Interface	Semi-transparent GUI
Control Mode	IR remote control, control panel, network
Video Systems	NTSC/PAL
Total Resource	4 Ch. D1
Resolution	PAL: D1 (704 × 576), HD1 (704 × 288), CIF (352 × 288) NTSC:D1(704×480), HD1(704×240), CIF(352×240)
Compression	H.264/G.726
Audio Input	4 Channels (DIN-JACK × 4)
Audio Output	2 Channels (DIN-JACK × 4)
Video Input	4 Channels (DIN-JACK × 4)
Video Output	2 Channels (DIN-JACK × 4)
Recording Mode	General/schedule/alarm (sensor trigger, speed, acceleration, video loss, temperature)
Pre-recording	1 ~ 60 minutes
Post-recording	30 ~ 1800 seconds

Features

- Total resource 4Ch full D1
- Gps Option
- H.264 video compression
- 3G/WiFi options for live view/record & alarm
- Removable HDD (up to 1TB)
- Pre-recording max. 15 mins
- Built-in GPS
- Tamper-proof watermarks



Active System Integration

www.asi.ind.in

Technical Specification

Watermark	Prevents the video file to be tampered
Image Quality	1~8 levels adjustable (1 is the best)
Sensors	8 Inputs, 4 Output
USB	USB 2.0 X 2
Hard Disk	2.5" SATA HDD
LAN	RJ45 cable supporting TCP/IP protocol
3G Support	HSDPA/EVDO
WiFi Support	Optional (External Only)
Storage	32G SD tested and Sandisk and Kingston brands are recommended (class 4)
Ethernet	RJ45 port (10/100M)
Serial Ports	RS232 × 2, RS485 × 2
Power Input	8 ~36 VDC
Power Output	12V max 2A; 5V max 2A
Power Consumption	< 15W (without cameras and any accessories)
Dimensions(WxHxD)	212 × 175 × 62mm
Operating Temperature	-10°C ~+ 65°C (please use built-in heater if the temperature is below 0°C)
Relatively Operating Humidity	8%~90%
Vibration Resistance	< 2 Grms
Shock Resistance	< 1200 Grms
Certifications	CE, FCC