



Active System Integration

## CP-TAR-1604H2D

H.264 Video Compression

[www.asi.ind.in](http://www.asi.ind.in)



### Features

- Full channel CIF Realtime Recording
- H.264 Dual-Stream Video Compression
- Pentaplex operation: Preview, recording, playback, backup, network
- HDMI / VGA / TV Simultaneous Video Output
- Support 2 SATA HDD, 2 USB2.0, 1 RS485, 1 DVDRW
- Multi DVR Client
- Mobile Software: MSS

### Technical Specification

Processor	High Performance Embedded Microprocessor
Operating System	Embedded LINUX
System Resources	Pentaplex function: : Preview, recording, playback, backup, network
User Interface	GUI
Video Input	BNC x 16
Video Output	1 TV Out, 1 Spot Out, 1 VGA, 1 HDMI
Compression	H.264



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

Video Resolution	704*576/352*288(PAL), 704*480/352*240(NTSC)
Video Recording	2CIF@(1-25fps)
Video Display Split	1/4/8/9/16
Audio Input	4 Ch
Bi-directional Talk Input	1 Ch. audio input
Audio Output	1 Ch x RCA
Motion Detection	Supports
Video Loss	Supports
Alarm Input	16 ch
Alarm Output	1 Ch
Hard Disk	2 SATA HDD Max upto 3 TB
Trigger Events	Record, PTZ move, e-mail, etc
Recording Mode	Manual, Timer, Motion
Search Mode	Time/calendar search, event (motion)
Playback	16 CH
Backup Mode	USB, network



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

Interface Ports	1 RS485, 1 RJ45, 2 USB2.0
Max user Account	18 users online,dual stream
Smart Phone	Windows phone, Symbian,Google phone, Blackberry and Iphone, compatible with 3G
Protocols	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS,E-mail
Ethernet	RJ45
Power Supply	DC: 12V
Working Temp	0°C~50°C
Working Humidity	10%~90%
Dimensions	430mm(W) * 300mm(D) * 55mm(H)