



Active System Integration

CP-UNC-DP13FC

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 1.3 Megapixel CMOS
Minimum Illumination	0.1lux/F1.4
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	Off/BLC/HLC/DWDR
Lens	2.8~12mm
S/N Ratio	More than 50 dB
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream: 1.3M(1-15fps), 720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)

Features

- 1/3" 1.3 Megapixel CMOS image sensor
- H.264 & MJPEG dual-stream encoding
- Max 15fps@1.3M(1280×960)&25/30fps@720P(1280×720)
- Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- 2.8~12mm varifocal lens
- Built-in 1/1 alarm in/out
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Privacy Masking	Up to 4 areas
Smart Phone	iPhone, iPad, Android, Windows Phone
ICR	Auto(ICR) / Color / B/W
Audio Input	1 Ch
Audio Output	1 Ch
Audio Compression	G.711a / G.711u (64kbps)/ PCM(128kbps)
Alarm IN	1 Ch.
Alarm Out	1 Ch.
Interface	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour. ONVIF Ver. 2.0
User Account	10 users
Micro SD	Micro SD, Max 32GB
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V, PoE(802.3af)
Power Consumption	Max.4W
Weatherproof Standard	IP66
Dimension	φ114 x 86mm
Weight	0.288kg