



Active System Integration

CP-UNC-TP13L3C

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 1.3Megapixel PS CMOS
Minimum Illumination	0.1lux/F1.4
Shutter Speed	Auto/Manual 1/3~1/10000
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC
Lens	6mm fixed Lens (3.6mm, 8mm optional)
S/N Ratio	More than 50 dB
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream: 1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas

Features

- 1/3" 1.3MP PS CMOS Image Sensor
- H.264 and MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280×960) and 25/30fps@720P(1280×720)
- Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- 6mm fixed Lens (3.6mm, 8mm optional)
- IR Range of 30Mtr.
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Interface	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour. ONVIF Ver. 2.0
User Account	10 Users
IR	IR Range of 30 Mtr
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V,PoE (802.3af)
Power Consumption	< 4W
Weatherproof Standard	IP66
Regulatory	CE, FCC and RoHS
Dimension	89.1mm × 200.2mm× 80.4mm
Weight	0.43kg