



Active System Integration

CP-UNC-DY20FL2C

H.264 Video Compression

www.asi.ind.in



Features

- 1/3" 2Megapixel progressive scan Exmor CMOS
- H.264 & MJPEG dual-stream encoding
- 25/30fps@1080P(1920×1080)
- 3.3~12mm varifocal lens
- DWDR, Day/Night(ICR), 2DNR, AWB, AGC, BLC
- Supports PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro

Technical Specification

Image Sensor	1/3" 2Megapixel Exmor CMOS
Minimum Illumination	Color: 0. 1Lux/F1.2, B/W: 0.01Lux/F1.2
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	Off/BLC/HLC/DWDR
Lens	3.3~12mm
S/N Ratio	More than 50dB
Video Compression	H.264 / MJPEG
Video Streaming	1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Video Output	10 Users
Resolution	1080P(1920×1080) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Channel
Audio Output	1 Channel
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	1 Channel
Alarm Out	1 Channel
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	10 Users
IR	IR Range of 20 Mtr.
Micro SD	SD, Max 32GB
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V, PoE(802.3af)
Power Consumption	< 6W
Regulatory	CE, FCC and RoHS
Dimension	Φ140.3mm x 113.7mm
Weight	0.8kg