



Active System Integration

CP-UNC-T5342FL3

H.264 Video Compression

www.asi.ind.in



Technical Specification

| | |
|----------------------|---|
| Image Sensor | 1/3" 3MP Progressive scan CMOS |
| Minimum Illumination | Color: 0.1Lux/F1.2, 0Lux/F1.2(IR on) |
| Shutter Speed | Auto/Manual, 1/3(4)~1/10000s |
| White Balance | Auto/Manual |
| AGC Control | Auto/Manual |
| Back Light Comp | BLC / HLC / DWDR |
| Lens | 2.7 -12mm Lens |
| Video Compression | H.264/MJPEG |
| S/N Ratio | More than 50dB |
| Video Streaming | Main Stream: 3M(1~20fps)/1080P/720P(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps) |
| Resolution | 3M(2048× 1536) / 1080P(1920× 1080) / 720P(1280× 720) / D1(704× 576) / CIF(352× 288) |
| Privacy Masking | Up to 4 areas |

Features

- 1/3" 3MP PS CMOS Image Sensor
- Max 20fps@3M and 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.7 -12mm Varifocal Lens
- IR Range of 30 Mtrs, Micro SD, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

| | |
|-----------------------|--|
| ICR | Auto(ICR)/Color/B/W |
| Smart Phone | iPhone, iPad, Android, Windows Phone |
| Audio Input | 1 Channel |
| Audio Output | 1 Channel |
| Audio Compression | G.711a/ G.711u/ PCM |
| Alarm IN | 1 Channel |
| Alarm Out | 1 Channel |
| Protocol | IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI |
| User Account | 20 Users |
| IR | IR Range of 30 Mtr |
| Micro SD | Micro SD, Max 64GB |
| Operating Temperature | -20°C~+60°C , Less than 90%RH |
| Power Source | DC12V (AC 24V optional), PoE (802.3af) |
| Power Consumption | Max 7W |
| Weatherproof Standard | IP66 |
| Dimension | φ104mm×306.7mm |
| Weight | 1.25Kg |