



Active System Integration

CP-UNC-T8373L3

H.264 Video Compression

www.asi.ind.in



Features

- 1/3" 3MP PS CMOS Image Sensor
- Max 25/30fps@3MP
- H.264 and MJPEG dual-stream encoding
- Ultra WDR, Ultra Defog, ROI, EIS, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- 2.7 -12mm Varifocal Lens
- IR Range of 30 Mtrs, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro

Technical Specification

Image Sensor	1/3" 3MP Progressive scan CMOS
Minimum Illumination	0. 1Lux/F1.2 (Color), 0.01Lux/F1.2(B/W);0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
AGC control	Auto/Manual
Back Light Comp	BLC / HLC / WDR (120dB)
Lens	2.7 -12mm
S/N Ratio	More than 50 dB
Video Compression	H.264/MJPEG
Video Streaming	Main Stream:3M/1080P (1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	3M(2048× 1536) / 1080P(1920× 1080) / 720P(1280× 720) / D1(704× 576) / CIF(352× 288)
Privacy Masking	Up to 4 areas



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Audio Input	1 channel
Audio Output	1 channel
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	1 Channel
Alarm Out	1 Channel
Interface	RJ-45 (10/100Base-T) & RS485
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI
Micro SD	Max 64GB
Operating Temperature	-20°C~+60°C , Less than 90%RH
Power Source	DC12V(AC24V optional), PoE (802.3af)
Power Consumption	Max 12W
WeatherProof Standard	IP66
Dimension	273.3mm × 94.8mm× 94.8mm
Weight	1.3 Kg