



Active System Integration

## CP-UNC-D2322L2

H.264 Video Compression

www.asi.ind.in



### Features

- 1/3" 3Megapixel progressive scan CMOS Image Sensor
- Max 12fps@3M or 25/30fps@1080P/720P
- H.264 and MJPEG dual-stream encoding
- Day/Night(ICR), 2D-DNR, AWB, AGC, BLC
- 3.6mm fixed lens (6mm optional)
- IR Range of 20 Mtrs, IP66
- Max 32GB Hot-swappable SD Card for Local Storage
- Built-in Web server, CMOB & KVMS(CMS)

### Technical Specification

Image Sensor	1/3" 3Megapixel progressive scan CMOS
Minimum Illumination	0.1Lux/F1.6 (Color) ;0Lux/F1.6(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
Lens	3.6mm (6mm optional)
Gain Control(AGC)	Auto/Manual
S/N Ratio	More than 50 dB
Video Compression	H.264/MJPEG



Active System Integration

www.asi.ind.in

## Technical Specification

Resolution	3M(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)
ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	10 Users
IR	IR Range of 20 mtr
Operating Temperature	-30°C~+60°C/ Less than 95%RH (no condensation)
Power Source	DC12V, PoE (802.3af)
Power Consumption	< 4.8W
WeatherProof Standard	IP66
Dimension	Φ93.8 x 82.2mm
Weight	360g