



Active System Integration

CP-UNC-V4352

H.264 Video Compression

www.asi.ind.in



Features

- 1/3" 3 MP Progressive Scan CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 20fps@3M(2048x1536), 25/30fps@1080P
- DWDR, Day/Night, 3D-DNR, AWB, AGC, BLC
- 3.6mm fixed lens (2.8mm, 6mm optional)
- Supports PoE, IP66, IK10
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro

Technical Specification

Image Sensor	1/3" 3 Megapixel CMOS
Minimum Illumination	0.01 Lux@F1.2
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto/Manual
AGC control	Auto/Manual
Back Light Comp	Off/BLC/HLC/DWDR
Lens	3.6mm fixed lens (2.8mm,6mm optional)
S/N Ratio	More than 50 dB
Video Compression	H.264/MJPEG
Video Streaming	Main Stream:3M(1~20fps)/1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	3.0M(2048 x 1536) /1080P(1920 x 1080) / 720P(1280 x 720) /D1(704 x 576) / CIF(352 x 288)
Privacy Masking	Up to 4 areas



Active System Integration

www.asi.ind.in

Technical Specification

Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	20 Users
Micro SD	Max 32GB, local storage
Operating Temperature	-20°C~+60°C/ Less than 95%RH
Power Source	DC12V, PoE (802.3af)
Power Consumption	< 3W
WeatherProof Standard	IP66 & IK10
Regulatory	CE, FCC, RoHs
Dimension	Φ110mm×54mm
Weight	0.25kg