



Active System Integration

CP-UNC-VY10FL2C

H.264 Video Compression

www.asi.ind.in



Features

- 1/3" 1.3 Megapixel progressive scan SONY CCD
- H.264 & MJPEG dual-stream encoding
- Max 12/15fps@1.3M(1280×720)&25/30fps@720P(1280x720)
- Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- 2.8~12mm varifocal lens
- Built-in 2/1 alarm in/out
- Max. IR Distance: 20m

Technical Specification

Image Sensors	1/3" 1.3Megapixel PS CCD
Minimum Illumination	0.2lux/F1.4(color),0.01Lux/F1.4(B/W),0Lux(IR on)
Shutter Speed	Auto/Manual,1/50~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC
Lens	2.8~12mm
Video Compression	H.264, MJPEG
S/N ratio	more than 50dB
Video Streaming	Main Stream: 1.3M(1~12fps)/720P(1 ~ 25fps), Sub Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480)/ CIF(352×288)
Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Privacy Masking	Up to 4 areas



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR) / Color / B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Channel
Audio Output	1 Channel
Audio Compressions	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	2 Channel
Alarm Out	1 Channel
Interface	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP,SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	10 Users
IR	IR Range Max upto 20m
Micro SD	SD, Max 32GB.
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V/AC24V, PoE(802.3af)
Power Consumption	< 10W
Weatherproof Standard	IK10 & IP66
Regulatory	CE, FCC & RoHs
Dimensions	Φ160mm×118.5mm
Weight	1.25kg