



Active System Integration

CP-UNP-2013MPL10

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" Exmor CMOS
Effective Pixels	1280(H) x 960(V), 1.3 Megapixels
S/N Ratio	More than 50dB
Focal Length	4.7mm ~ 94mm
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Angle of View	H: 54°~3.2°
Focus Control	Auto / Manual
Electronic Shutter	1/1 ~ 1/30,000s
AGC control	Auto / Manual
Back Light Compensation	BLC / HLC /DWDR
Privacy Masking	Up to 24 areas

Features

- 1/3" Exmor CMOS Image Sensor
- 1.3MP Image Quality
- Powerful 20x Optical Zoom
- Pan range: 360° endless, speed up to 60°/s
- Up to 256Presets, 4Tour, 4Pattern, 4Auto scan
- IR Distance up to 100 Mtr., IP66
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

Optical Zoom	20x
Digital Zoom	16x
Smart Phone	iPhone, iPad, Android, Windows Phone
Pan Travel	360° endless, 0.1° ~ 60°/sec
Tilt Travel	-90° ~ 90°, 0.1° ~30°/sec
Presets	256
Preset Accuracy	±0.02°
Special Features	Up to 256 Presets, 4Tour, 4 Pattern, 4 Auto scan, Preset Auto-Calibration, Remote P/T/Z Reset, Wiper, IR Range of 100 Mtr.
Day/Night: IR Cut Filter	Auto(ICR) / Color / B/W
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream:25/30fps@1.3M/720P, Sub Stream: 25/30fps@D1/CIF
Networking	RJ-45 (10/100Base-T)
Protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	20 users
Operating Temperature	-30°C ~ 65°C / Less than 90% RH
Weather Proof Standard	IP66, All-metal aluminum alloy, 6000V anti-lightning surge
Weight	8.5Kg
Power Source	DC 8V~36V
Power Consumption	< 60W