



Active System Integration

CP-UNP-1813L10D

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" CCD
Effective Pixels	1280(H) x 960(V)
Synchronization	Internal
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC
S/N Ratio	More than 50dB
Minimum illumination	0.05Lux/F1.6
Focal Length	4.7mm~84.6mm
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Angle of View	H: 55.2°~3.2°
Focus Control	Auto/Manual
Electronic Shutter	PAL:1/3~1/10000s NTSC:1/4~1/10000s
AGC control	Auto / Manual
Back Light Compensation	BLC / HLC / WDR
Privacy Masking	Up to 24 areas
Remote Operations	Monitor, PTZ control, Voice Intercom, System setting, Playback
Optical Zoom	18x
Digital Zoom	12x
Smart Phone	iPhone, iPad, Android, Windows Phone

Features

- 1/3" CCD
- H.264 & MJPEG dual-stream encoding
- Powerful 18x optical zoom and 12x digital zoom
- WDR, Day/Night(ICR), DNR (2D&3D),Auto iris, Auto focus, AWB, AGC,BLC
- Max. 25/30fps @1.3M(1280×960) & 720P resolution
- Max 400°/s pan speed, 360° endless pan rotation
- Up to 255 presets, 5 auto scan, 8 tour, 5 pattern
- Build-in 7/2 channel alarm input/output



Technical Specification

Manual Speed	Horizontal: 0.1°~300°/s, Vertical: 0.1°~150°/s
Presets	255
Preset Speed	Pan: 400°/s; Tilt: 300°/s
Special Features	WDR, Day/Night(ICR), DNR (2D&3D),Auto iris, Auto focus, 5 Auto Pattern, 8 Auto Tour, 5 auto scan
Power up action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Pan/ Scan/ Tour/ Pattern if there is no command in the specified period
Time task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Day/Night: IR Cut Filter	Auto(ICR) / Color / B/W
Video Compression	H.264 / MJPEG
Audio Compression	G.711a / G.711u(32kbps)/ PCM(128kbps)
Audio Streaming	1/1 channel In/Out
Networking	RJ-45 (10/100Base-T), 1 RS485
Alarm	7/2 channel In/Out
Supported Web Browser	Windows – Microsoft Internet Explorer 6.x or later
User Account	20 Users simultaneously
Operating Temperature	-40°C ~ 60°C
Dimensions	Φ222(mm) x 322 (mm)
Weight	5.0kg
Power Source	AC 24V/3A(±10%)