



Active System Integration

CP-VTA-L2024C-R

Direct Lock Support

www.asi.ind.in



Technical Specification

Processor	TI Stellaris® 32-Bit High Speed CPU
Fingerprint Capacity	2000
Log Capacity	50000
Sensor	Optical Sensor
Scan Area	22mm*18mm
FRR	0.001%
FAR	0.00001%
LCD	128*64mm Blue LCD
Identification Mode	FP, ID+FP, ID+PW, FP+PW

Features

- New generation fully sealed, waterproof and dustproof fingerprint sensor.
- USB & TCP/IP network interface
- Advanced Algorithm for Reliable operation
- Stylish blue LCD. Musical buzzer
- Direct Lock Support
- Supports 2000 fingerprints
- Multiple identification method: fingerprint only, ID + password, ID + fingerprint



Active System Integration

www.asi.ind.in

Technical Specification

Identification Time	< 1 second
Resolution	500 DPI
Fingerprint Image Display	Yes
Communication	TCP/IP, USB device and host
Self-defined Status	16
Work Code	Yes
Operating Temperature	-10°C-60°C
Recommended no. of users	Up to 1000 Employees
ESD Tolerance	>15000V
Humidity	20%-80%
Certifications	FCC, CE, RoHs
Operating Voltage	DC5V
Dimension	185(w)*130(h)*35(d)mm