



Active System Integration

CP-VTA-T3027C

Reliable Data Transfer and Optional

www.asi.ind.in



Technical Specification

Processor	TI high speed CPU
Fingerprint Capacity	3000
Log Capacity	50000
Sensor	Optical Sensor
Scan Area	22mm*18mm
FRR	0.001%
FAR	0.00001%
LCD	3" widescreen High Definition TFT display
Identification Mode	FP, Card, ID+FP, ID+PW, PW+Card, FP+Card

Features

- Extremely Thin and Refined Design
- 3" widescreen High Definition TFT display
- New generation fully sealed, waterproof and dustproof fingerprint sensor
- Fast fingerprint scan in less than 0.5 second
- USB & TCP/IP connectivity
- Realtime data transfer and optional WEB server
- Various employee authentication methods. Easy combination of fingerprint, password and card



Active System Integration

www.asi.ind.in

Technical Specification

Identification Time	< 0.5 Sec
Resolution	500 DPI
Fingerprint Image Display	Yes
Realtime Transfer	Yes
Communication	USB & TCP/IP
Self-defined Status	Yes
Work Code	6-digit word code
Daylight Saving	Yes
Operating Temperature	-10°C-40°C
Recommended no. of users	Up to 1500 Users
Short Message	Yes
Certifications	FCC, CE
Operating Voltage	DC5V