



Active System Integration

DH-NVR608-128-4K 608R-128-4K

128 channel Super 4k Network video recorder

www.asi.ind.in



Features

- Max 128 channel IP cameras connection
- Max 384Mbps incoming bandwidth
- Up to 12Mp resolution preview & playback
- Support 8 hot-swap HDDs
- Support RAID 0/1/5/6/10/50/60
- Support iSCSI to expand storage space
- Support RAID 0/1/5/6/10/50/60
- Support N+M hot standby
- ONVIF Version 2.4 conformance
- Redundant power supply module adopted (DH-NVR608R-64-4K)

Technical Specification

Model	DH-NVR608-128-4K	DH-NVR608R-128-4K
System		
Main Processor	Intel Processors	
Operating System	LINUX	
Video & Audio		
IP Camera Input	64 channel	
Two-way Talk	1channel Input, 1channel Output, RCA	
Display		
Interface	2 HDMI (up to 3840x2160), 1 VGA	
Resolution	3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768	
Multi-screen Display	The 1st screen: 1/4/8/9/16/25/36	
	The 2nd screen: 1/4/8/9/16	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	



Active System Integration

www.asi.ind.in

Technical Specification

Auxiliary Interface		
USB	4 USB ports(3 USB2.0, 1 USB3.0)	
eSATA	1 eSATA port	
RS232	1 port, For PC communication& keyboard	
RS485	1 port, For PTZ control	
General		
Power Supply	AC110V~240V, 50~60Hz	AC100V~240V, 50~60Hz, Redundant
Power Consumption	<40W (Without HDD)	
Working Environment	-10°C~+55°C/10%~90%RH/86~106kpa	
Dimension(WxDxH)	486mm(with ears)x454.9mm x91mm	486mm(with ears)x471.8mm x91mm
Weight	9kg (without HDD)	
Installation	19" Rack-mounted	